

Our best selling pneumatic heat press



Digital Controller



Pneumatic Pressure Control



Swing Head Operation



230 Volt AC Mains Operation

Features:

- Swing-head operation for a clear view of the working area.
- Fully adjustable and accurate air pressure gauge control.
- Locking air pressure control.
- Emergency stop button.
- LED digital microprocessor controller.
- Thermal cut out on the heating element if the temperature exceeds 235°C +/- 15°C.
- LM6 cast aluminium construction for strength and durability.
- Self adhesive silicone base pad.
- Manufactured and tested to comply with EC safety regulations. CE labelled.
- Lifetime heat element guarantee with 12 month warranty on machine.
- Full service/ spares support.
- Manual supplied illustrates electrical wiring diagram, exploded diagram and parts list.
- Full safety instructions.

Machine Info:

The Major is the pinnacle of our Beta Range. Ideally suited to high volume production environments, where exact, repeatable pressure is required, then this pneumatically operated swing-away press is an absolute must have piece of equipment.

The high quality LM6 cast aluminium press base houses the pneumatic cylinder. This means the Major has a minimal number of moving parts internally, making it highly reliable. The pressure is user controlled via a simple air pressure adjustment dial. Fully adjustable time and temperature are set via the touch pad display and the emergency stop button ensures safety at all times

Optional Tables:

15.3 cm x 15.3 cm, 20.5 cm x 20.5 cm
 25.4 cm x 25.4 cm, 30.5 cm x 30.5 cm
 30.5 cm x 15.3 cm, 38 cm x 38 cm,
 Umbrella table

Beta Major



Power consumption.....	2.5 kW
Power supply.....	230 Volts AC
Compressed air supply.....	7 bar max
Compressed air consumption.....	60 litres/min
Working temperature.....	0 - 235°C
Display timer range.....	0 - 9.59 min
Machine height.....	52 cm
Machine width.....	59 cm
Machine width, loading.....	79 cm
Machine depth.....	57 cm
Machine depth, loading.....	104 cm
Work area required.....	80(W) x 52(H) x 105(D) cm
Weight export packed.....	77 Kg
Net weight.....	69 Kg
Press pad dimensions.....	38 cm x 50 cm
Fuse.....	12.5 A
A-weighted noise level.....	<70 dB(A)

The Beta Major eliminates operator fatigue with pneumatic operation